

1. Detecting your first Community Structure

To detect communities, you can use the `cdlib` package. It also contains functions for evaluation and comparison of partitions. For details, check the documentation at <https://cdlib.readthedocs.io/en/latest/>

!!! With google colab, you can install it with `!pip install cdlib`, but, due to a colab bug, you also need to do first:

```
!pip uninstall python-louvain validate with y, then !pip install python-louvain.
```

- (a) Using `networkx`, load the airport dataset, provided as a graphml file. (reminder: you can download it in colab with `!wget URL` with `URL` the url of the file.
- (b) Using `cdlib`, detect communities on this network using the louvain method. You have to use the `algorithms.louvain` method (and do `from cdlib import algorithms` before).
- (c) Visualize the communities found. In order to interpret them, you should draw each node at its geographical location, with a color per community.

There are several ways to draw a spatial network with colors corresponding to communities, from using Gephi to plotting points on an interactive map using `folium`. Here, I provide a simple code to plot the data as a simple scatter plot

Listing 1: plot on a map

```
import seaborn as sns
import matplotlib.pyplot as plt
x= list(nx.get_node_attributes(g,"lon").values())
y= list(nx.get_node_attributes(g,"lat").values())

coms_dict=coms.to_node_community_map()
hues=list(coms_dict[n][0] for n in g.nodes())

plt.figure(figsize=(12,8))
sns.scatterplot(x=x,y=y,hue=hues,palette=sns.color_palette("tab20",len(coms.communities)),s=5)
```

- (d) Vary the resolution parameter and observe changes in the community structure.

2. Comparing Partitions

- (a) The provided airport data also contains information about the country of each airport, which can be interpreted as a *ground truth* partition of the network. You can obtain it using `nx.get_node_attributes(g,"country")`. Transform this information into a `NodeClustering` object of `cdlib` (`nc = NodeClustering(partition,graph,"GroundTruth")`, with `partition` a list of list of nodes.
- (b) Compute the AMI, NMI, or another similarity score (<https://cdlib.readthedocs.io/en/latest/reference/evaluation.html>) between the community structure and the partition in countries

- (c) By exploring with a for loop the values of the resolution parameter for modularity, find the partition with the highest similarity to the partition in countries.
- (d) Compare visually the results